

TECHNICAL DATA SHEET

JOKISCH MIGMA RINO EGR (Jokisch Anti foam fluid WMK)

Highly effective defoamer for water soluble Mineral oil-containing / free cooling lubricants.

Chlorine free - amine free - nitrite free - free of boric acid - free of biocides

APPLICATION

Premixed with water or existing emulsion. Add to highly turbulent place (but not before the filter). Before each new addition it is necessary to wait until a thorough mixing has occurred (should be added in portions). The defoamer should be added until a sufficient foam collapse occurred.

CHARACTERISTICS

Provides maximum compatibility with the usual subsequent processes. After washing machined parts can be painted or coated without problems.

PROPOSED CONCENTRATION

We recommend a concentration of 0,01% - 0,02%


TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH MIGMA RINO EGR
Kin. viscosity at 20°C	mm ² /s	ASTM D 7042	29-34
Density at 20°C	g/cm ³	DIN EN ISO 12185	1,04
pH-value at 20°C	-	DIN 51369	8,1

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this.

STORAGE

Storage temperature: 5 – 40°C
Storage time: 12 months



JosS d.o.o.

General Distributor for Slovenia, Croatia, BiH, Serbia,
Montenegro, Kosovo and North Macedonia

Sokolska 45 | 2000 Maribor | Slovenia
T +386 2 421 57 20 | GSM +386 41 705 509
joss@joss.si | www.joss.si

