

TECHNICAL DATA SHEET

JOKISCH MONOS PRIX F2G

Multifunction grease for various industrial application.

High strained roller bearings, which work under difficult conditions, including shock load, in damp locations.

APPLICATION

Multi-purpose grease with EP properties for high loads, on the basis of a lithium-hydroxystearate thickener and with proven additives for reliable performance. It is ideal for lubricating rolling elements and bearings and it is very well transportable in central lubrication systems.

CHARACTERISTICS

- Outstanding load carrying capacity
- Improved mechanical stability
- Resistant to water wash off
- Oxidation stability
- Good corrosion protection properties

Suitable for the application temperature range from -20°C to + 130°C.

Care must be taken to ensure that elastomers are compatible with mineral oil (hydrocarbons). Rubber and rubber components in brake systems designed for non-mineral hydraulic fluids (e.g., polyglycol based) may be incompatible.


TECHNICAL SPECIFICATIONS

	UNIT	METHOD	JOKISCH MONOS PRIX F2G
NLGI consistency			2
Thickener			Lithium
Base oil type			Mineral oil
Kin. viscosity at 40°C	cSt	IP 71 / ASTM D445	220
Kin. viscosity at 100°C	cSt	IP 71 / ASTM D445	19
Cone penetration, worked	0.1mm	IP 50 / ASTM D217	265-295
Dropping point	°C	IP 396	180

This information is based on the latest state of knowledge. They are intended to describe the product and thus do not have the meaning to assure certain properties. A liability can not be derived from this

STORAGE

Storage temperature: 5 – 40°C
Storage time: 36 months



JosS d.o.o.

General Distributor for Slovenia, Croatia, BiH, Serbia,
Montenegro, Kosovo and North Macedonia

Sokolska 45 | 2000 Maribor | Slovenia
T +386 2 421 57 20 | GSM +386 41 705 509
joss@joss.si | www.joss.si

