



JosS d.o.o.  
Sokolska 45 | 2000 Maribor | Slovenia  
T +386 2 421 57 20 | GSM +386 41 705 509  
joss@joss.si | www.joss.si

## Technical Data Sheet

- Low Emissions
- Maintenance Saving

# Shell Rimula R5 LM 10W-40

## Heavy Duty Diesel Engine Oil

Shell Rimula R5 LM oils feature "Low-SAPS" additive technology. Protective power enhances oil performance to deliver responsive protection, resulting in maintenance saving and long oil drain capability



### Performance, Features & Benefits

- **Emissions system capability**  
Advanced low-ash formulation helps control blocking of or poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.
- **Maintenance saving**  
Shell Rimula R5 LM has been formulated to meet the long oil drain requirements of Mercedes-Benz to allow operators to optimize maintenance scheduling.
- **Improved engine cleanliness**  
The advanced formulation delivers good engine cleanliness and protection against piston deposits allowing Shell Rimula R5 LM to ensure engine and component reliability at extended oil drain intervals.

- **European heavy duty engines**

Shell Rimula R5 LM provides protection and performance in modern high-power heavy-duty diesel engines from leading European engine makers such as Mercedes-Benz and where oils meeting ACEA E8 are called for.

- **Low emission engine use**

Shell Rimula R5 LM meets the requirements of Mercedes-Benz for modern engine applications.

### Specifications, Approvals & Recommendations

- ACEA E6, E8
- DTFR 15C110
- Meets requirements of DAF (meets ACEA E6)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

### Main Applications



### Typical Physical Characteristics

Properties			Method	Shell Rimula R5 LM 10W-40
Kinematic Viscosity	@40°C	mm <sup>2</sup> /s	ASTM D445	98.8
Kinematic Viscosity	@100°C	mm <sup>2</sup> /s	ASTM D445	14.5
Dynamic Viscosity	@-25°C	mPa s	ASTM D5293	6 133
Viscosity Index			ASTM D2270	152
Total Base Number		mg KOH/g	ASTM D2896	10.4
Sulphated Ash		%	ASTM D874	1.0
Density	@15°C	kg/l	ASTM D4052	0.866
Flash Point (COC)		°C	ASTM D92	232
Pour Point		°C	ASTM D97	-42

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

- **Health and Safety**

Shell Rimula R5 LM 10W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.