

Eco FUN-TAK® Mounting Putty

DESCRIPTION

Loctite® Eco FUN-TAK® Mounting Putty is a reusable, repositionable adhesive that is a convenient sustainable alternative for tape, tacks, staples and magnets for use at home, school and the office. An excellent solution for temporary mounting, Eco Fun-Tak Mounting Putty is great for hanging lightweight items like posters or party decorations without creating holes in walls or chipping paint. It is also unaffected by moisture and will not dry out for long-lasting use. Loctite Eco Fun-Tak is versatile and sticks to paper, wood, tile, linoleum, cinderblock, brick, metal, plastic, mirrors, and glass. Designed for interior use only, this product is made with 96% naturally derived sustainable components, is non-toxic and safe for children.

Available as:

Item #	Package	Size
2989019	Carded Blister – Mounting Putty Tabs	4 oz. (113 g)
2975164	Carded Blister – Mounting Putty	2 oz. (57 g)

FEATURES & BENEFITS

- Eco-Friendly: No Pigments, preservatives, or biocides. Outer packaging is made of 75% recycled board and is recyclable
- Reusable: Long-lasting removable mounting putty will not dry out for multiple uses
- Convenient Sustainable Alternative: Use in place of nails, tape, tacks, staples, and magnets for hanging lightweight items
- No Holes: Eliminate making and repairing holes in walls or cracking and chipping paint
- Nontoxic: Non-toxic formula and safe for children

RECOMMENDED FOR

- Bonding items up to 1 lb. in weight to most smooth surfaces including blackboards, wood, brick, glass, tile, metal, porcelain, linoleum, and concrete/cinderblock
- Hanging children's artwork on the refrigerator, attach memos to the phone, stick recipes, party decorations, and greeting cards to the wall
- Stopping vibrations of rattling windows, secure candlesticks, paper tablecloths, shelf paper and drawer linings, secure desk blotters and accessories

LIMITATIONS

DO NOT USE FOR:

- Hanging heavy objects, such as mirrors and framed pictures
- Sticking items to textured wall surfaces, flocked or paper wall coverings, on peeling or newly painted surfaces
- Mounting costly artwork and posters
- Exterior applications

TECHNICAL DATA

Typical Physical Properties		Typical Application Properties	
<u>Color:</u>	Light grey	<u>Application Temperature:</u>	For best performance use and maintain at room temperature
<u>Appearance:</u>	Putty	<u>Specifications:</u>	Conforms to ASTM D4236
<u>Base:</u>	Synthetic Rubber	<u>Odor:</u>	Minimal

DIRECTIONS

Preparation:

Surfaces must be clean and dry.

Application:

Tear off enough Loctite Eco FUN-TAK Mounting Putty for the job and knead the putty until soft and warm. Place a small amount between surfaces to be fastened and press. **IMPORTANT:** When using Mounting Putty Tabs, use 4 tabs per 1 lb. of weight.

IMPORTANT: Test first on absorbent surfaces. If uncertain, test in an inconspicuous area for 24 hours. May leave oily stain on some papers and flat painted surfaces. To remove, gently peel away items from mounting surface. Do not pull the putty off wall surfaces as damage may occur. Should any putty particles remain, simply roll more Eco FUN-TAK over area until clean.

Clean up:

To remove any excess putty residue, roll additional mounting putty over the surface area to pick up any remaining particles. Adhesive remover may assist in removal of oily stains.

STORAGE & DISPOSAL

Not damaged by freezing. Dispose of unwanted putty with trash.

LABEL PRECAUTIONS

Not classified as hazardous

Note: this product contains natural rubber

Refer to the Safety Data Sheet (SDS) for further information

DISCLAIMER

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Henkel recommends purchasers/users should test the products to determine acceptable quality and suitability for the intended use. All adhesive/sealant applications should be tested under simulated or actual end use conditions to ensure the adhesive/sealant meets or exceeds all required project specifications. Since assembly conditions may be critical to adhesive/sealant performance, it is also recommended that testing be performed on specimens assembled under simulated or actual production conditions. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

LIMITED WARRANTY

This product is warranted by Henkel Corporation to be free from defects in materials when used as directed. Henkel's sole obligation shall be, at its option, to replace or refund the purchase price of product proven to be defective. Henkel makes no other warranty – express or implied – including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE and will not be liable for consequential or incidental damages. This Limited Warranty gives you specific legal rights, which vary from state to state. For warranty assistance, contact Henkel at 1.800.624.7767 M-F 9:00 am to 4:00 pm EST.



Trusted Performance. Proven Results.

For over 50 years, LOCTITE Brand adhesives and sealants have taken on the toughest jobs. Used in race cars, airplanes, and even in the space-shuttle, LOCTITE provides solutions for the most demanding industrial, professional and consumer applications. LOCTITE gives you the specialization, power, and performance to not only get your job done, but to get it done right.

For Technical Assistance call : 1-800-624-7767 – Mon-Fri - 9:00a – 4:00p ET

www.loctiteproducts.com



LOCTITE Brand is part of the Henkel family of brands. Founded in 1876, Henkel is a global leader in the consumer and industrial businesses. Henkel operates worldwide with leading brands and technologies in three business areas: Laundry & Home Care, Beauty Care and Adhesive Technologies.

Henkel Corporation - Professional & Consumer Adhesives Headquarters - Rocky Hill, CT 06067

www.henkel-northamerica.com

